




2-1926733-5 Product Details

[Share](#) [Print](#) [Email](#)



Obsolete
[View 3D PDF](#)

MINIPAK HDL Connectors

AssyMinipak Hdl25s10pRAREcptSc

2-1926733-5

TE Internal Number: 2-1926733-5

Product Highlights [View All](#)

- Connector Style = Receptacle
- 25/Signal, 10/DC Power
- 25 Signal Positions
- 10 Power Positions
- 35 Positions

[Pricing & Availability](#)

[Request Sample](#)

[Add to My Part List](#)

[Buy Product through Distributor](#)

[Documents](#)[Features](#)[Compliance](#)

<p>Please Note: Use the Product Drawing for all design activity</p>															
<p>Product Type Features</p> <table border="1"> <tr><td>PCB Mount Retention Type</td><td>Screw Mount</td></tr> <tr><td>PCB Mount Alignment</td><td>Without</td></tr> <tr><td>PCB Mount Retention</td><td>With</td></tr> <tr><td>PCB Mounting Orientation</td><td>Right Angle</td></tr> <tr><td>Make First / Break Last</td><td>Yes</td></tr> <tr><td>Product Line</td><td>MINIPAK HDL</td></tr> <tr><td>Sealed</td><td>No</td></tr> </table>		PCB Mount Retention Type	Screw Mount	PCB Mount Alignment	Without	PCB Mount Retention	With	PCB Mounting Orientation	Right Angle	Make First / Break Last	Yes	Product Line	MINIPAK HDL	Sealed	No
PCB Mount Retention Type	Screw Mount														
PCB Mount Alignment	Without														
PCB Mount Retention	With														
PCB Mounting Orientation	Right Angle														
Make First / Break Last	Yes														
Product Line	MINIPAK HDL														
Sealed	No														
<p>Housing Features</p> <table border="1"> <tr><td>Connector Style</td><td>Receptacle</td></tr> <tr><td>Centerline (mm [in])</td><td>2.00 [0.079]</td></tr> <tr><td>Centerline, Power Contacts (mm [in])</td><td>2.75 [0.108]</td></tr> <tr><td>Mating Alignment</td><td>With</td></tr> <tr><td>Housing Material</td><td>Crystal Polymer</td></tr> <tr><td>Housing Color</td><td>Black</td></tr> <tr><td>Mating Alignment Type</td><td>Passive Guide</td></tr> </table>		Connector Style	Receptacle	Centerline (mm [in])	2.00 [0.079]	Centerline, Power Contacts (mm [in])	2.75 [0.108]	Mating Alignment	With	Housing Material	Crystal Polymer	Housing Color	Black	Mating Alignment Type	Passive Guide
Connector Style	Receptacle														
Centerline (mm [in])	2.00 [0.079]														
Centerline, Power Contacts (mm [in])	2.75 [0.108]														
Mating Alignment	With														
Housing Material	Crystal Polymer														
Housing Color	Black														
Mating Alignment Type	Passive Guide														
<p>Electrical Characteristics</p> <table border="1"> <tr><td>Operating Voltage Reference</td><td>DC</td></tr> <tr><td>Operating Voltage (VAC)</td><td>250</td></tr> <tr><td>Hot Pluggable</td><td>No</td></tr> <tr><td>UL Voltage Rating (VAC)</td><td>250</td></tr> </table>		Operating Voltage Reference	DC	Operating Voltage (VAC)	250	Hot Pluggable	No	UL Voltage Rating (VAC)	250						
Operating Voltage Reference	DC														
Operating Voltage (VAC)	250														
Hot Pluggable	No														
UL Voltage Rating (VAC)	250														
<p>Configuration Features</p> <table border="1"> <tr><td>Connector Contact Configuration (No. of Pos./Type)</td><td>25/Signal, 10/DC Power</td></tr> <tr><td>Number of Signal Positions</td><td>25</td></tr> <tr><td>Number of Power Positions</td><td>10</td></tr> <tr><td>Number of Positions</td><td>35</td></tr> <tr><td>Number of Rows</td><td>1</td></tr> <tr><td>Tail Orientation</td><td>In-line</td></tr> <tr><td>Custom Configurable</td><td>No</td></tr> </table>		Connector Contact Configuration (No. of Pos./Type)	25/Signal, 10/DC Power	Number of Signal Positions	25	Number of Power Positions	10	Number of Positions	35	Number of Rows	1	Tail Orientation	In-line	Custom Configurable	No
Connector Contact Configuration (No. of Pos./Type)	25/Signal, 10/DC Power														
Number of Signal Positions	25														
Number of Power Positions	10														
Number of Positions	35														
Number of Rows	1														
Tail Orientation	In-line														
Custom Configurable	No														
<p>Termination Features</p> <table border="1"> <tr><td>Termination Method to PC Board</td><td>Through Hole - Press Fit</td></tr> </table>		Termination Method to PC Board	Through Hole - Press Fit												
Termination Method to PC Board	Through Hole - Press Fit														
<p>Dimensions</p> <table border="1"> <tr><td>Tail Length (mm [in])</td><td>3.3 [0.13]</td></tr> <tr><td>PCB Thickness, Recommended (mm [in])</td><td>1.40 [0.055]</td></tr> <tr><td>Length (X-Axis) (mm [in])</td><td>51.71 [2.040]</td></tr> <tr><td>Width (Z-Axis) (mm [in])</td><td>36.58 [1.440]</td></tr> <tr><td>Profile Height (Y-Axis) (mm [in])</td><td>8.00 [0.315]</td></tr> </table>		Tail Length (mm [in])	3.3 [0.13]	PCB Thickness, Recommended (mm [in])	1.40 [0.055]	Length (X-Axis) (mm [in])	51.71 [2.040]	Width (Z-Axis) (mm [in])	36.58 [1.440]	Profile Height (Y-Axis) (mm [in])	8.00 [0.315]				
Tail Length (mm [in])	3.3 [0.13]														
PCB Thickness, Recommended (mm [in])	1.40 [0.055]														
Length (X-Axis) (mm [in])	51.71 [2.040]														
Width (Z-Axis) (mm [in])	36.58 [1.440]														
Profile Height (Y-Axis) (mm [in])	8.00 [0.315]														
<p>Industry Standards</p> <table border="1"> <tr><td>RoHS/ELV Compliance</td><td>Not ELV/RoHS compliant</td></tr> <tr><td>Lead Free Solder Processes</td><td>Not relevant for lead free process</td></tr> <tr><td>Agency/Standard</td><td>CSA, UL</td></tr> <tr><td>UL Rating</td><td>Recognized</td></tr> <tr><td>UL File Number</td><td>E28476</td></tr> <tr><td>UL Flammability Rating</td><td>UL 94V-0</td></tr> <tr><td>CSA Certified</td><td>Yes</td></tr> </table>		RoHS/ELV Compliance	Not ELV/RoHS compliant	Lead Free Solder Processes	Not relevant for lead free process	Agency/Standard	CSA, UL	UL Rating	Recognized	UL File Number	E28476	UL Flammability Rating	UL 94V-0	CSA Certified	Yes
RoHS/ELV Compliance	Not ELV/RoHS compliant														
Lead Free Solder Processes	Not relevant for lead free process														
Agency/Standard	CSA, UL														
UL Rating	Recognized														
UL File Number	E28476														
UL Flammability Rating	UL 94V-0														
CSA Certified	Yes														
<p>Body Features</p> <table border="1"> <tr><td>Selectively Loaded</td><td>Yes</td></tr> <tr><td>Mating Retention</td><td>Without</td></tr> </table>		Selectively Loaded	Yes	Mating Retention	Without										
Selectively Loaded	Yes														
Mating Retention	Without														
<p>Contact Features</p> <table border="1"> <tr><td>Contact Plating, Termination Area, Material</td><td>Bright Tin-Lead</td></tr> </table>		Contact Plating, Termination Area, Material	Bright Tin-Lead												
Contact Plating, Termination Area, Material	Bright Tin-Lead														
<p>Environmental</p> <table border="1"> <tr><td>Operating Temperature (°C [°F])</td><td>-40 - +125 [-40 - +257]</td></tr> </table>		Operating Temperature (°C [°F])	-40 - +125 [-40 - +257]												
Operating Temperature (°C [°F])	-40 - +125 [-40 - +257]														