


Item no.: 234-508
 Product description: PCB TERMINAL STRIP 2 SOLDER PINS / POLE 8 POLE PIN
 SPACING 2.54 MM / 0.1 IN WITH PUSH BUTTONS FRONT-
 ENTRY CAGE CLAMP®CONNECTION



Packing unit 220 4*55 pieces

Product group	4 (Printed Circuit)
Pin spacing from	2,54 mm
Pin spacing from	0,1 in
pole count	8
Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	0,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	20 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	2,5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	3,85 g
Color	orange
Wiring type	Front-entry
No. of connection Points	8
No. of potentials	8
Height	14 mm
Height	0,551 in
Width	22,52 mm
Width	0,887 in



Depth	14,4 mm
Depth	0,567 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0,22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
234-508	ABS	04-HG469925-PDA	250	4	0,8-0,5
234-508	BV	11915/A0	250	6	0,08-0,5
234-508	CSA	154112-1465035	150	4	28-20
234-508	DEMKO	118980ES	250	6	0,5
234-508	DEMKO	DK96-03660	250	4	0,8-0,5
234-508	DNV	E-9215	250	4	0,8-0,5
234-508	GL	17296-00HH	250	4	0,8-0,5
234-508	KEMA	90.6212.01/02	250	6	0,08-0,5
234-508	NEMKO	L87192	125	4	0,5
234-508	RMR	11130002	250	4	0,8-0,5
234-508	SEMKO	9043004	250		0,5
234-508	UR	E45172	150	4	28-20

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected