



Silicon PNP transistors, general purpose  
Transistors PNP silicium, usage général

T<sub>amb</sub> = 25 °C

Type	Case Boîtier	P <sub>tot</sub> (mW)	V <sub>CEO</sub> (V) V <sub>CER</sub> * V <sub>CEX</sub> □	h <sub>21E</sub> h <sub>21E</sub> min	max	I <sub>C</sub> (mA)	V <sub>CEsat</sub> (V) max	I <sub>C</sub> /I <sub>B</sub> (mA)	f <sub>T</sub> (MHz) min	t <sub>s</sub> (ns) t <sub>off</sub> max	TSi 76 Page
2N 1131	TO 39	600	-35	20	45	-150	-1,5	150/15	50		131
2N 1132	TO 39	600	-35	30	90	-150	-1,5	150/15	50		131
*2N 2904	TO 39	600	-40	40	120	-150	-1,5	500/50	200	175*	229
*2N 2904 A	TO 39	600	-60	40	120	-150	-1,5	500/50	200	175*	229
*2N 2905	TO 39	600	-40	100	300	-150	-1,5	500/50	200	200*	229
*2N 2905 A	TO 39	600	-60	100	300	-150	-1,5	500/50	200	200*	229
*2N 2906	TO 18	400	-40	40	120	-150	-1,6	500/50	200	175*	235
*2N 2906 A	TO 18	400	-60	40	120	-150	-1,6	500/50	200	175*	235
*2N 2907	TO 18	400	-40	100	300	-150	-1,6	500/50	200	200*	235
*2N 2907 A	TO 18	400	-60	100	300	-150	-1,6	500/50	200	200*	235
2N 3702	TO 92○	360	-25	60	300	-50	-0,25	50/5	100		#
2N 3703	TO 92○	360	-30	30	150	-50	-0,25	50/5	100		#
2N 3905	TO 92○	350	-40	50	150	-10	-0,4	50/5	200	200	#
2N 3906	TO 92○	350	-40	100	300	-10	-0,4	50/5	250	225	#
2N 4058	TO 92○	360	-30	100	400	-0,1	-0,7	10/0,5			#
2N 4059	TO 92○	360	-30	45	660	-1	-0,7	10/0,5			#
2N 4060	TO 92○	360	-30	45	165	-1	-0,7	10/0,5			#
2N 4061	TO 92○	360	-30	90	330	-1	-0,7	10/0,5			#
2N 4062	TO 92○	360	-30	180	660	-1	-0,7	10/0,5			#
2N 4125	TO 92○	350	-30	50	150	-2	-0,4	50/5	200		#
2N 4126	TO 92○	350	-25	120	360	-2	-0,4	50/5	250		#
2N 5365	TO 92○	360	-40	40	120	-50	-1	300/30	250§		289
2N 5366	TO 92○	360	-40	100	300	-50	-1	300/30	250§		289
*2N 5447	F 139 B○	360	-25	60	300	-50	-0,25	50/5	100		293
*2N 5448	F 139 B○	360	-30	30	150	-50	-0,25	50/5	100		293
BC 160	TO 39	650	-40	40	250	-100	-1	1000/100	50		313
BC 161	TO 39	650	-60	40	250	-100	-1	1000/100	50		313
*BC 177 VI	TO 18	300	-45	75*	150*	-2	-0,95	100/5	200§		319
*BC 177 A	TO 18	300	-45	125*	260*	-2	-0,95	100/5	200§		319
*BC 178 VI	TO 18	300	-25	75*	150*	-2	-0,95	100/5	200§		319
*BC 178 A	TO 18	300	-25	125*	260*	-2	-0,95	100/5	200§		319
*BC 178 B	TO 18	300	-25	240*	500*	-2	-0,95	100/5	200§		319
BC 179 A	TO 18	300	-20	125*	260*	-2	-0,95	100/5	200§		319
BC 179 B	TO 18	300	-20	240*	500*	-2	-0,95	100/5	200§		319
*BC 212	F 139 B○	300	-50	60	300	-2	-0,6	100/5	200		347

\* Preferred device      § Typical value      ○ Plastic case      # To be published later  
Dispositif recommandé      Valeur typique      Boîtier plastique      Sera publiée ultérieurement