

MALE HEADER

MALE HEADER STRAIGHT DOUBLE ROW 2.54 mm

STRIP HEADERS



Features	Breakable header Insulator profile 2.6 mm Pin side dimension 0.6 mm
Material	Insulator: High temperature thermoplastic UL 94V0 Contact: Phosphor bronze
Electrical	Current rating: 4A maxi Dielectric withstanding: 1000 V AC Insulation resistance: 1000 MΩ mini
Mechanical	Temperature rating: -40 °C to 125 °C Pc board Hole diameter Ø 1 mm
Packaging	Recyclable cardboard boxes

Product Code

A	B	C	D
473	xxxx	1xx	4x0

B	Version
C	Number of contacts from 02 to 90
D	Plating 0 Gold 0.2 µm over Ni 1.27 µm 4 Tin 4 µm over Ni 1.27 µm Other platings on demand

Version	A	B	C
0358	11.2	5.4	3.2
1955	11.2	5.8	2.8
0334	12.4	6.8	3
2801	12.9	7.3	3
0369	13.8	7.7	3.5
2035	13.8	7.7	3.5
2754	14.5	8.8	3.1
2256	15.1	9.3	3.2
2581	16.3	10.9	2.8
0575	17.7	12	3.1
1960	17.7	9.3	5.8
0211	22	15.5	3.8
2804	30.8	25.2	3
0395	15.1	8	4.5
0298	10.2	4.5	3.2
0543	9.2	3.3	3.3
0303	19.5	12	4.9
0307	30.8	22.4	5.8
0306	28.3	19.9	5.8
0305	25.8	17.4	5.8
0304	23.3	14.9	5.8
1844	16.3	7.9	5.8
1958	14.5	6.1	5.8
1956	12.4	4	5.8

(N= Number of contacts)

