

16K CMOS Static RAM (16384x1) 20PIN 6167

型名	社名	温度範囲 (°C)	スイッチング特性									電源		入力[*typ]			出力[*typ]			備考	
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWR max (ns)	VDD or VCC (V)	I DD max (mA)	I DD STANDBY (I SB/I SB2) (mA)	VIL max (V)	VIH min (V)	Ci max (pF)	VOL/I VOL max (V/mA)		VOH/I VOH min (V/mA)
51C66-25	INTEL	0~70	25	15		0	15	20	15	3	0	4.5~5.5	80	20/-	0.8	2.2	5	0.4/12	2.4/1	7	
51C66-30	INTEL	0~70	30	20		0	20	20	15	3	0	4.5~5.5	80	20/-	0.8	2.2	5	0.4/12	2.4/1	7	
51C66-35	INTEL	0~70	35	20		0	20	20	15	3	0	4.5~5.5	80	20/-	0.8	2.2	5	0.4/12	2.4/1	7	
51C66-35L	INTEL	0~70	35	20		0	20	20	15	3	0	4.5~5.5	80	60/-	0.8	2.2	5	0.4/12	2.4/1	7	
51C67-35	INTEL	0~70	35			0	25	20	15	3	0	4.5~5.5	100	10/-	0.8	2.2	5	0.4/12	2.4/8	7	
CY7C167-25	CYPRESS	0~70	25	25		3	15	15	0	0	0	4.5~5.5	60		0.8	2	4	0.4/12	2.4/4	6	
CY7C167-35	CYPRESS	0~70	35	35		3	20	20	0	0	0	4.5~5.5	60		0.8	2	4	0.4/12	2.4/4	6	
CY7C167-45	CYPRESS	0~70	45	45		3	25	20	0	0	0	4.5~5.5	50		0.8	2	4	0.4/12	2.4/4	6	
CY7C167A-20	CYPRESS	0~70	20	20			8	15	10	0	0	4.5~5.5	80	40/-	0.8	2.2	4	0.4/12.0	2.4/4.0	6	
CY7C167A-25	CYPRESS	0~70	25	25			10	15	10	0	0	4.5~5.5	60	20/-	0.8	2.2	4	0.4/12.0	2.4/4.0	6	
CY7C167A-35	CYPRESS	0~70	35	35			15	20	15	0	0	4.5~5.5	60	20/-	0.8	2.2	4	0.4/12.0	2.4/4.0	6	
CY7C167A-45	CYPRESS	0~70	45	45			15	20	15	0	0	4.5~5.5	50	15/-	0.8	2.2	4	0.4/12.0	2.4/4.0	6	
HM6167/P	HITACHI	0~70	70	70		5	30	40	30	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6167/P-6	HITACHI	0~70	85	85		5	40	45	35	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6167/P-8	HITACHI	0~70	100	100		5	40	55	40	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6167H-45	HITACHI	0~70	45	45		5	30	25	25	0		4.5~5.5	80	2/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167H-55	HITACHI	0~70	55	55		5	30	35	25	0		4.5~5.5	80	2/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167H/HP-70	HITACHI	0~70	70	70		5	30	40	30	0	0	4.5~5.5	60	2/-	0.8	2.2	5	0.4/8	2.4/4	7	
HM6167HLP-45	HITACHI	0~70	45	45		5	30	25	25	0		4.5~5.5	80	0.05/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167HLP-55	HITACHI	0~70	55	55		5	30	35	25	0		4.5~5.5	80	0.05/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167HP-45	HITACHI	0~70	45	45		5	30	25	25	0		4.5~5.5	80	2/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167HP-55	HITACHI	0~70	55	55		5	30	35	25	0		4.5~5.5	80	2/-	0.8	2.2	5	0.4/-	2.4/-	7	
HM6167LP	HITACHI	0~70	70	70		5	30	40	30	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6167LP-6	HITACHI	0~70	85	85		5	40	45	35	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6167LP-8	HITACHI	0~70	100	100		5	40	55	40	0	0	4.5~5.5	60	20/-	0.8	2.2		0.4/8	2.4/4		
HM6267CG-35	HITACHI	0~70	35			5	30	20	20	0		4.5~5.5	80	20/-	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267CG-45	HITACHI	0~70	45			5	30	25	25	0		4.5~5.5	80	20/-	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267LP-35	HITACHI	0~70	35			5	30	20	20	0		4.5~5.5	80	20/-	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267LP-45	HITACHI	0~70	45			5	30	25	25	0		4.5~5.5	80	20/-	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267LP-55	HITACHI	0~70	55	55		5		35	25	0	0	4.5~5.5	80	20/0.5	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267P-35	HITACHI	0~70	35	35		5	30	20	20	0	0	4.5~5.5	80	20/2	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267P-45	HITACHI	0~70	45	45		5	30	25	25	0	0	4.5~5.5	80	20/2	0.8	2.2	5	0.4/8	2.4/4	7	
HM6267P-55	HITACHI	0~70	55	55		5		35	25	0	0	4.5~5.5	80	20/20	0.8	2.2	5	0.4/8	2.4/4	7	
HM65261-2	MHS	-55~125	85	85			40	55	35	0	0	4.5~5.5	50	4/0.9	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261-5	MHS	0~70	70	70			30	50	30	0	0	4.5~5.5	50	3/0.05	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261-9	MHS	-40~85	70	70			30	50	30	0	0	4.5~5.5	50	4/0.4	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261B-2	MHS	-55~125	70	70			30	50	30	0	0	4.5~5.5	50	4/0.5	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261B-5	MHS	0~70	60	60			30	45	25	0	0	4.5~5.5	40	3/0.05	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261C-2	MHS	55~125	100	100			40	60	40	0	0	4.5~5.5	60	5/4	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261C-5	MHS	0~70	85	85			40	55	35	0	0	4.5~5.5	60	4/2	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261C-9	MHS	-40~85	85	85			40	55	35	0	0	4.5~5.5	60	5/3	0.8	2.2	8	0.4/8	2.4/4	10	
HM65261S-2	MHS	-55~125	70	70			30	50	30	0	0	4.5~5.5	60	5/4	0.8	2.2	8	0.4/8	2.4/4	10	