

AZ832P

POLARIZED DIP RELAY BISTABLE (LATCHING)

FEATURES

- High sensitivity, 42 mW pickup
- Low profile DIP package
- Meets FCC Part 68.302 1500 V lightning surge
- Meets FCC Part 68.304 1000 V dielectric
- Single and dual coil versions
- DC coils to 24 VDC
- High switching capacity, 60 W, 250 VA
- Fits standard 16 pin IC socket
- Epoxy sealed for automatic wave soldering and cleaning
- UL, CUR file E43203



CONTACTS

Arrangement	DPDT (2 Form C) Bifurcated crossbar contacts
Ratings	Resistive load: Max. switched power: 60 W or 250 VA Max. switched current: 2 A Max. switched voltage: 250 VDC or 250 VAC
Rated Load UL	2 A at 30 VDC resistive 2 A at 125 VAC resistive
Material	Gold plated silver against gold plated silver
Resistance	< 50 milliohms initially

COIL

Power	
At Pickup Voltage (typical)	Standard coil: 56 mW Sensitive coil: 42 mW
Max. Continuous Dissipation	0.9 W at 20°C (68°F)
Temperature	Max. 115°C (239°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Relay has fixed coil polarity.
4. For complete isolation between the relay's magnetic fields, it is recommended that a .197" (5.0 mm) space be provided between adjacent relays.
5. Relay adjustment may be affected if undue pressure is exerted on relay case.
6. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 2 x 10 ⁷ 1 x 10 ⁵ at 2 A, 30 VDC or 1 A, 125 VAC 2 x 10 ⁶ at 1 A, 30 VDC or .5 A, 125 VAC
Set Time (typical)	3 ms at nominal coil voltage
Reset Time (typical)	3 ms at nominal coil voltage
Bounce (typical)	3 ms
Dielectric Strength (at sea level)	1500 Vrms contact to coil 1000 Vrms between contact sets 1000 Vrms across contacts Meets FCC Part 68.302 lightning surge Meets FCC Part 68.304 V dielectric
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC, 50% RH
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 85°C (185°F) -40°C (-40°F) to 115°C (239°F)
Vibration	50 g at 10–500 Hz
Shock	50 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	5 grams



AMERICAN ZETTLER, INC. www.azettler.com


75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

AZ832P

RELAY ORDERING DATA

STANDARD SINGLE COIL				
COIL SPECIFICATIONS				ORDER NUMBER
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Set Reset VDC	
3	9.0	90	2.25	
5	15.0	250	3.75	
12	36.0	1,440	9.0	
24	60.0	4,000	18.0	
SENSITIVE SINGLE COIL				
2.25	7.8	67.5	1.69	AZ832P1-2C-2.25DSE
3	10.4	120	2.25	AZ832P1-2C-3DSE
5	17.2	330	3.75	AZ832P1-2C-5DSE
12	41.6	1,920	9.0	AZ832P1-2C-12DSE
24	83.1	7,680	18.0	AZ832P1-2C-24DSE
STANDARD DUAL COIL				
COIL SPECIFICATIONS				ORDER NUMBER
Nominal Coil VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$	Set Reset VDC	
3	6.4	45	2.25	
5	10.6	125	3.75	
6	12.7	180	4.5	
12	25.5	720	9.0	
24	42.8	2,040	18.0	
SENSITIVE DUAL COIL				
3	7.3	60	2.25	AZ832P2-2C-3DSE
5	12.3	167	3.75	AZ832P2-2C-5DSE
6	14.7	240	4.5	AZ832P2-2C-6DSE
12	29.4	960	9.0	AZ832P2-2C-12DSE
24	58.8	3,840	18.0	AZ832P2-2C-24DSE

MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance: $\pm .010"$



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM