

AZ6991

SENSITIVE SUBMINIATURE RELAY

FEATURES

- Extremely small footprint utilizing only 0.22 square inch of PCB area
- Thin vertical profile only 0.196" wide, horizontal version available
- 8 Amp switching capability
- High sensitivity, 95 mW pickup
- Dielectric strength 4000 Vrms contact to coil
- Coils to 60 VDC
- Epoxy sealed version for wave soldering and cleaning available
- Isolation spacing greater than 8 mm
- UL, CUR file E43203,
- VDE file 40020561



CONTACTS

Arrangement	SPST (1 Form A) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: 180 W or 1662 VA Max. switched current: 6 A Max. switched voltage: 150* VDC or 400 VAC Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Rated Load UL/CUR	8A at 277 VAC resistive (Form A and C N.O.) 6A at 277 VAC resistive (Form C N.C.) 6A at 30 VDC resistive R300, B300 Pilot Duty
VDE	6A at 250 VAC resistive 6A at 30 VDC resistive
Material	Silver nickel, Silver Tin Optional gold plating
Resistance	< 50 milliohms initially (24 V voltage drop method)

COIL

Power At Pickup Voltage (typical)	95 mW
Max. Continuous Dissipation	1.0 W at 20°C (68°F) ambient
Temperature Rise	20°C (36°F) at nominal coil voltage
Temperature	Max. 105°C (221°F)

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 10 million operations 3 X 10 ⁴ at 6 A, 30 VDC or 250 VAC Res.
Operate Time (typical)	8 ms at nominal coil voltage
Release Time (typical)	4 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	1000 Vrms between open contacts 4000 Vrms contact to coil
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 10% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 85°C (158°F) -40°C (-40°F) to 105°C (221°F)
Vibration	0.062" DA 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester 94V-0
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	260°C (500°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	5.4 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM


AZ6991

RELAY ORDERING DATA

COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance	Unsealed	Sealed
3	2.25	6.9	53 ± 10%	AZ6991-1A-3D	AZ6991-1A-3DE
5	3.75	11.5	147 ± 10%	AZ6991-1A-5D	AZ6991-1A-5DE
6	4.50	13.8	212 ± 10%	AZ6991-1A-6D	AZ6991-1A-6DE
9	6.75	20.7	476 ± 10%	AZ6991-1A-9D	AZ6991-1A-9DE
12	9.00	27.6	848 ± 10%	AZ6991-1A-12D	AZ6991-1A-12DE
18	13.5	41.4	1906 ± 15%	AZ6991-1A-18D	AZ6991-1A-18DE
24	18.0	55.2	3390 ± 15%	AZ6991-1A-24D	AZ6991-1A-24DE
48	36.0	97.7	10600 ± 15%	AZ6991-1A-48D	AZ6991-1A-48DE
60	45.0	122.2	16600 ± 15%	AZ6991-1A-60D	AZ6991-1A-60DE

*Substitute "-1C" for "-1A" to indicate 1 Form C contacts. Add "E" after 1A or 1C for Silver Tin contacts. Add suffix "A" for gold plated contacts. Add suffix "H" for horizontal version.

MECHANICAL DATA



Dimensions in inches with metric equivalents in parentheses. Tolerance: ± .010"



AMERICAN ZETTLER, INC.

www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM