



STEEL C 60 EN 10132

DIMENSIONS AND FEATURES						PACKAGING		
For screws of	d min.-max.	D min.-max.	s min.-max.	No. of teeth	Kg/1000 pieces	No. of pcs standard packaging	No. of pcs bulk packaging	No. of pcs micro packaging
M 2.0	2.20-2.34	4.20-4.50	0.27-0.33	9	0.027	5000	180000	1000
M 2.3	2.50-2.64	4.70-5.00	0.36-0.44	9	0.041	5000	140000	1000
M 2.5	2.70-2.84	5.20-5.50	0.36-0.44	9	0.048	5000	125000	1000
M 3.0	3.20-3.38	5.70-6.00	0.36-0.44	9	0.058	2000	100000	500
M 3.5	3.70-3.88	6.64-7.00	0.46-0.54	10	0.101	2000	65000	500
M 4.0	4.30-4.48	7.64-8.00	0.46-0.54	11	0.129	2000	45000	500
M 5.0	5.10-5.28	8.64-9.00	0.46-0.54	11	0.147	1000	35000	200
M 5.0	5.30-5.48	9.64-10.00	0.55-0.65	11	0.228	1000	20000	200
M 6.0	6.40-6.62	10.57-11.00	0.65-0.75	12	0.290	1000	17500	200
M 7.0	7.40-7.62	12.07-12.50	0.75-0.85	14	0.440	1000	12000	200
M 8.0	8.20-8.42	13.57-14.00	0.75-0.85	14	0.515	1000	10000	200
M 8.0	8.40-8.62	14.57-15.00	0.75-0.85	14	0.678	1000	7500	200
M 10.0	10.50-10.77	17.57-18.00	0.85-0.95	16	1.020	1000	5000	100
M 12.0	13.00-13.27	19.98-20.50	0.94-1.06	16	1.260	1000	3500	100
M 14.0	15.00-15.27	23.48-24.00	0.94-1.06	18	1.906	500	2000	100
M 16.0	17.00-17.27	25.48-26.00	1.14-1.26	18	2.559	500	1500	100
M 18.0	19.00-19.33	29.48-30.00	1.34-1.46	18	4.270	250	900	
M 20.0	21.00-21.33	32.38-33.00	1.34-1.46	20	5.300	250	750	
M 22.0	23.00-23.33	35.38-36.00	1.42-1.58	20	6.530	200	650	
M 24.0	25.00-25.33	37.38-38.00	1.42-1.58	20	6.901	150	600	
M 27.0	28.00-28.33	43.38-44.00	1.52-1.68	22	8.787	100	450	
M 30.0	31.00-31.39	47.38-48.00	1.52-1.68	22	11.620	100	350	

Dimensions in mm

Technical details:

Hardness of material: 350 - 425 Hv.
Tightening couples: see table.
Chemical analysis of raw material: see table.

Anticorrosion surface covering:

Burnishing and light oiling.
Zinc plating 6-8 my Cr6 free
Yellow zinc plating 6-8 my Cr6 free
Other finishings by request.

Features and specific use:

Washer with overlapped teeth for fasteners with limited tightening couples.