

Series 49SMD Crystal • E49B

20.000H708

This part is a miniature AT cut strip crystal units with a low profile package. It is with resistance weld.

FEATURES

- Low Cost
- Industry Standard
- Wide Frequency Range
- Excellent Aging

Crystal units

Electrical Specifications


	Туре	E49B			
Frequency Range	F0	3.2~66.000MHz			
Load Capacitance	CL	10pF to Series			
Frenqency Tolerance	$\bigtriangleup F/F0$	± 10 ppm, ± 30 ppm, ± 50 ppm(At 25 °C)			
Equivalent Series Resistance	ESR	See Table 1			
Temperature Stability	TC	\pm 10ppm, \pm 30ppm, \pm 50ppm(Refer to 25 °C)			
Operating Temperature Range	TOPR	−20~+70°C,−30~+85°C Option			
Storage Temperature Range	TSTG	−55~+125°C			
Shunt Capacitance	C0	7pF max.			
Insulator Resistance	IR	500MΩ min. (At 100VDC)			
Drive Level	DL	100μW(500μW max.)			
Aging	Fa	±5ppm max. (At 25°C,First year)			
Packing Unit		200pcs/bag			

Table 1:Equivalent Series Resistance(ESR) and Mode of Vibration(Mode)


Frequency Range(Mhz)	Max ESR(Ω)	Mode	Frequency Range(Mhz)	Max ESR(Ω)	Mode
3.200 to 4.499	150	Fundamental/AT	9.000 to 9.999	60	Fundamental/AT
4.500 to 5.999	120	Fundamental/AT	10.000 to 12.999	50	Fundamental/AT
6.000 to 6.999	100	Fundamental/AT	13.000 to 40.000	40	Fundamental/AT
7.000 to 7.999	90	Fundamental/AT	40.000 to 66.000	80	3 rd Overtone
8.000 to 8.999	80	Fundamental/AT			

**Please contact us for inquiries regarding other Specifications

Mechanical Dimensions(mm)







11

TAIWAN: HOSONIC ELECTRONIC CO., LTD. 23-1 LANE 84. CHUN YING ST. SHULIN CHEN. TAIPEI 23804. TAIWAN WEB SITE:http://www.hosonic.com

2: 886-2-86875200 886-2-26816456 Dis hosonic.sales@hosonic.com HANGZHOU HOSONIC ELECTRONIC CO., LTD. NO.242 LIANGBO ROAD. LIANGZHU TOWN. YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA WEB SITE:http://www.hosonic.com



Specifications are subject to change without notice

CHINA: