


Features


- Switching-loss rating includes all "tail" losses
- Optimized for medium operating frequency (1 to 10kHz) See Fig. 1 for Current vs. Frequency curve



$V_{CES} = 900V$
 $V_{CE(sat)} \leq 4.3V$
 $@ V_{GE} = 15V, I_C = 5.3A$

Description

Insulated Gate Bipolar Transistors (IGBTs) from International Rectifier have higher usable current densities than comparable bipolar transistors, while at the same time having simpler gate-drive requirements of the familiar power MOSFET. They provide substantial benefits to a host of high-voltage, high-current applications.



Absolute Maximum Ratings

	Parameter	Max.	Units
V_{CES}	Collector-to-Emitter Voltage	900	V
$I_C @ T_C = 25^\circ C$	Continuous Collector Current	9.0	A
$I_C @ T_C = 100^\circ C$	Continuous Collector Current	5.3	
I_{CM}	Pulsed Collector Current ①	18	
I_{LM}	Clamped Inductive Load Current ②	18	
V_{GE}	Gate-to-Emitter Voltage	± 20	V
E_{AVR}	Reverse Voltage Avalanche Energy ③	5.0	mJ
$P_D @ T_C = 25^\circ C$	Maximum Power Dissipation	60	W
$P_D @ T_C = 100^\circ C$	Maximum Power Dissipation	24	
T_J	Operating Junction and	-55 to $+150$	$^\circ C$
T_{STG}	Storage Temperature Range		
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	
	Mounting torque, 6-32 or M3 screw.	10 lbf·in (1.1N·m)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
R_{eJC}	Junction-to-Case	—	—	2.1	$^\circ C/W$
R_{eCS}	Case-to-Sink, flat, greased surface	—	0.50	—	
R_{eJA}	Junction-to-Ambient, typical socket mount	—	—	80	
Wt	Weight	—	2.0 (0.07)	—	
					g (oz)

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage	900	—	—	V	$V_{GE} = 0V, I_C = 250\mu\text{A}$
$V_{(BR)ECS}$	Emitter-to-Collector Breakdown Voltage ^④	20	—	—	V	$V_{GE} = 0V, I_C = 1.0\text{A}$
$\Delta V_{(BR)CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	—	0.85	—	V/°C	$V_{GE} = 0V, I_C = 1.0\text{mA}$
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	—	2.9	4.3	V	$I_C = 5.3\text{A}, V_{GE} = 15\text{V}$
		—	3.5	—		$I_C = 9.0\text{A}, \text{See Fig. 2, 5}$
		—	3.5	—		$I_C = 5.3\text{A}, T_J = 150^\circ\text{C}$
		—	—	—		$V_{CE} = V_{GE}, I_C = 250\mu\text{A}$
$V_{GE(th)}$	Gate Threshold Voltage	3.0	—	5.5		
$\Delta V_{GE(th)}/\Delta T_J$	Temperature Coeff. of Threshold Voltage	—	-10	—	mV/°C	$V_{CE} = V_{GE}, I_C = 250\mu\text{A}$
g_{fe}	Forward Transconductance ^⑤	0.9	1.5	—	S	$V_{CE} = 100\text{V}, I_C = 5.3\text{A}$
I_{CES}	Zero Gate Voltage Collector Current	—	—	250	μA	$V_{GE} = 0V, V_{CE} = 900\text{V}$
		—	—	1000		$V_{GE} = 0V, V_{CE} = 900\text{V}, T_J = 150^\circ\text{C}$
I_{GES}	Gate-to-Emitter Leakage Current	—	—	± 100	nA	$V_{GE} = \pm 20\text{V}$

Switching Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
Q_g	Total Gate Charge (turn-on)	—	11	17	nC	$I_C = 5.3\text{A}$
Q_{ge}	Gate - Emitter Charge (turn-on)	—	2.6	3.9		$V_{CC} = 400\text{V}, \text{See Fig. 8}$
Q_{gc}	Gate - Collector Charge (turn-on)	—	4.6	6.9		$V_{GE} = 15\text{V}$
$t_{d(on)}$	Turn-On Delay Time	—	29	—	ns	$T_J = 25^\circ\text{C}$
t_r	Rise Time	—	12	—		$I_C = 5.3\text{A}, V_{CC} = 720\text{V}$
$t_{d(off)}$	Turn-Off Delay Time	—	170	300		$V_{GE} = 15\text{V}, R_G = 50\Omega$
t_f	Fall Time	—	120	280		Energy losses include "tail"
E_{on}	Turn-On Switching Loss	—	0.25	—	mJ	See Fig. 9, 10, 11, 14
E_{off}	Turn-Off Switching Loss	—	0.36	—		
E_{ts}	Total Switching Loss	—	0.61	1.10		
$t_{d(on)}$	Turn-On Delay Time	—	27	—	ns	$T_J = 150^\circ\text{C}, I_C = 5.3\text{A}, V_{CC} = 720\text{V}$
t_r	Rise Time	—	13	—		$V_{GE} = 15\text{V}, R_G = 50\Omega$
$t_{d(off)}$	Turn-Off Delay Time	—	270	—		Energy losses include "tail"
t_f	Fall Time	—	240	—		See Fig. 10, 14
E_{ts}	Total Switching Loss	—	1.10	—	mJ	Measured 5mm from package
L_E	Internal Emitter Inductance	—	7.5	—	nH	
C_{ies}	Input Capacitance	—	220	—	pF	$V_{GE} = 0V, V_{CC} = 30V, f = 1.0\text{MHz}, \text{See Fig. 7}$
C_{coes}	Output Capacitance	—	25	—		
C_{res}	Reverse Transfer Capacitance	—	3.4	—		

Notes:

① Repetitive rating; $V_{GE}=20\text{V}$, pulse width limited by max. junction temperature.
(See fig. 13b)

② $V_{CC}=80\%(V_{CES})$, $V_{GE}=20\text{V}$, $L=10\mu\text{H}$, $R_G=50\Omega$, (See fig. 13a)

③ Repetitive rating; pulse width limited by maximum junction temperature.

⑤ Pulse width 5.0μs, single shot.

④ Pulse width $\leq 80\mu\text{s}$; duty factor $\leq 0.1\%$.




Fig. 1 - Typical Load Current vs. Frequency
 (For square wave, $I=I_{\text{RMS}}$ of fundamental; for triangular wave, $I=I_{\text{PK}}$)




Fig. 2 - Typical Output Characteristics




Fig. 3 - Typical Transfer Characteristics




Fig. 4 - Maximum Collector Current vs. Case Temperature




Fig. 5 - Collector-to-Emitter Voltage vs. Case Temperature




Fig. 6 - Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig. 7 - Typical Capacitance vs. Collector-to-Emitter Voltage




Fig. 8 - Typical Gate Charge vs. Gate-to-Emitter Voltage




Fig. 9 - Typical Switching Losses vs. Gate Resistance




Fig. 10 - Typical Switching Losses vs. Case Temperature




Fig. 11 - Typical Switching Losses vs. Collector-to-Emitter Current




Fig. 12 - Turn-Off SOA

Refer to Section D for the following:

Appendix F: Section D - page D-8

- Fig. 13a - Clamped Inductive Load Test Circuit
- Fig. 13b - Pulsed Collector Current Test Circuit
- Fig. 14a - Switching Loss Test Circuit
- Fig. 14b - Switching Loss Waveform

Package Outline 1 - JEDEC Outline TO-220AB

Section D - page D-12