





**Terminal Layout
脚位图**



**Mounting Holes(mm)
安装尺寸**



CLASSIFICATION	PCB RELAY	
Appearance 外型	JZC-20F(4088)	
Outline Dimension(L×W×H) 外形尺寸(mm)	22.5×16.5×24	
Contact Form 触点形式	1A, 1C	
Contact Resistance 接触电阻	100mΩ	
Coil Voltage 线圈电压	5VDC~48VDC	
Pick-up Voltage 动作电压	≤75%	
Release Voltage 释放电压	≥10%	
Coil Power(W) 线圈功率(瓦)	0.36	
Contact Rating 触点容量	5A/10A 120VAC 5A/10A 28VDC 5A 240VAC	
Insulation Resistance 绝缘电阻	100MΩ	
Dielectric Strength 介质耐压	Between Open Contact 断开触点间	750VAC
	Between Coil and Contact 触点线圈间	1000VAC
Life 寿命	Electrical 电气	1×10 ⁵
	Mechanical 机械	1×10 ⁷
Temperature Range 使用温度	-40~+55℃	
Terminal Layout 脚位图		
Mounting Holes(mm) 安装尺寸		
Mounting Form 安装形式	PCB Terminal	
Weight 重量	13g	
Salty Approval 安全标准		
Cross-Reference 型号对照		