

16K nMOS Static RAM (16384x1) 20PIN 2167

型名	社名	温度範囲 (°C)	スイッチング特性										電 源			入力 [*typ]			出力 [*typ]			備 考	
			TAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWR max (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (ISB/ISB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/IVOL max (V/mA)	VOH/IOH min (V/mA)	Co max (pF)		
2167-55	INTEL	0~0	55	55		5	30	35	25	0	0	0	4.5~5.5	70		0.8	2.0	7	0.4/8	2.4/4	6		
2167-70	INTEL	0~0	70	70		5	40	40	30	0	0	0	4.5~5.5	70		0.8	2.0	7	0.4/8	2.4/4	6		
2167L-10	INTEL	0~0	100	100		5	40	45	35	0	5	5	4.5~5.5	50		0.8	2.0	7	0.4/8	2.4/4	6		
2167L-70	INTEL	0~0	70	70		5	40	40	30	0	0	0	4.5~5.5	50		0.8	2.0	7	0.4/8	2.4/4	6		
Am2167-45	AMD	0~70	40	45		5	25	20	15	5	5	0	4.5~5.5	120		0.8	2.0	5	0.4/16	2.4/4	6		
Am2167-55	AMD	0~70	50	55		5	30	25	20	5	5	0	4.5~5.5	120		0.8	2.0	5	0.4/16	2.4/4	6		
Am2167-70	AMD	0~70	70	70		5	40	40	30	5	5	0	4.5~5.5	120		0.8	2.0	5	0.4/16	2.4/4	6		
F3567-55	FSC		55										5	125									
HM65767-2	MHS	-55~125												50	20/-	0.8	2.0	4	0.4/8	2.4/4	6		
HM65767H-5	MHS	0~70	25	25			15	15	15	0	0		4.5~5.5	60	20/-	0.8	2.0	4	0.4/8	2.4/4	5		
HM65767K-2	MHS	-55~125	35	35			20	20	15	0	0		4.5~5.5	60	20/-	0.8	2.0	4	0.4/8	2.4/4	6		
HM65767K-5	MHS	0~70	30	35			20	20	15	0	0		4.5~5.5	60	20/-	0.8	2.0	4	0.4/8	2.4/4	6		
HM65767M-2	MHS	-55~125	40	45			25	20	15	0	0		4.5~5.5	50	20/-	0.8	2.0	4	0.4/8	2.4/4	6		
HM65767M-5	MHS	0~0	40	45			25	20	15	0	0		4.5~5.5	50	15/-	0.8	2.0	4	0.4/8	2.4/4	6		
IMS1400-35	INM	0~70	35	35		3	25	20	15	0	0	0	4.5~5.5	120		0.8	2.0	4	0.4/16	2.4/4	7		
IMS1400-45	INM	0~70	40	45		3	25	20	15	0	0	0	4.5~5.5	120		0.8	2.0	4	0.4/16	2.4/4	7		
IMS1400-55	INM	0~70	50	55		3	30	25	20	0	0	0	4.5~5.5	120		0.8	2.0	4	0.4/16	2.4/4	7		
IMS1400L-10	INM	0~70	95	100		5	40	45	35	5	0	5	4.5~5.5	90		0.8	2.0	4	0.4/16	2.4/4	7		
IMS1400L-70	INM	0~70	65	70		5	30	40	30	0	0	0	4.5~5.5	90		0.8	2.0	4	0.4/16	2.4/4	7		
MSM2167S-55	MITSUBISHI		55										5	120									
MSM2167S-70	MITSUBISHI		70										5	120									
MB81C67-35	FUJITSU	0~70	35	35		5	25			0	0		4.5~5.5	60		25/15	0.8	2.2	7	0.4/16	2.4/4	8	
MB81C67-45	FUJITSU	0~70	45	45		5	25			0	0		4.5~5.5	60		25/15	0.8	2.2	7	0.4/16	2.4/4	8	
MB81C67-55	FUJITSU	0~70	55	55		5	30			0	0		4.5~5.5	60		25/15	0.8	2.2	7	0.4/16	2.4/4	8	
MB8167-45	FUJITSU	0~70	45										5	132									
MB8167-55	FUJITSU	0~0	55	55									4.5~5.5	132		0.8	2.0	5	0.4/8	2.4/4	6		
MB8167-70	FUJITSU	0~0	70	70		5	40	45	45	0	10		4.5~5.5	132		0.8	2.0	5	0.4/8	2.4/4	6		
MB8167A-55	FUJITSU	-10~85	55	55		5	30	35	35	0	5	5	4.5~5.5	120		0.8	2.0	5	0.45/16	2.4/4	6		
MB8167A-70	FUJITSU	-10~85	70	70		5	40	45	45	0	10	10	4.5~5.5	120		0.8	2.0	5	0.45/16	2.4/4	6		
uPD2167D-2	NEC	0~70	70	70		5	40	40	30	10	0	15	4.5~5.5	180		0.8	2.0	5	0.4/8	2.4/4			
uPD2167D-3	NEC	0~70	55	55		5	40	35	25	10	0	10	4.5~5.5	180		0.8	2.0	5	0.4/8	2.4/4			