



## Male Double Row Vertical PC Tail

- Polarised mouldings.
- Fully shrouded contacts.
- Mates with female connectors shown on pages 21 to 24.
- For British Standard versions see pages 18 to 19.
- Can be used with Strain Relief straps:  
order code **M80-0030006**.




### UNLATCHED




### CALCULATION

<b>A</b>	$B + 5.60$
<b>B</b>	Total no. of contacts - 2




Recommended PC Board Pattern

### LOCKING LATCH



### FRICTION LATCH



### HOW TO ORDER

**M80 - XXX XX XX**

#### SERIES CODE

RoHS	Non-RoHS	
<b>854</b>	<b>869</b>	Unlatched (3mm tail)
<b>853</b>	<b>867</b>	Locking Latch (3mm tail)
<b>863</b>	<b>815</b>	Friction Latch (3mm tail)
<b>754</b>	<b>754</b>	Unlatched (4.5mm tail)
<b>753</b>	<b>753</b>	Locking Latch (4.5mm tail)
<b>763</b>	<b>763</b>	Friction Latch (4.5mm tail)

#### FINISH

<b>05</b>	Gold	
<b>22</b>	Gold + Tin/Lead	
<b>42</b>	Gold + Tin	
<b>45</b>	Gold	

#### TOTAL NO. OF CONTACTS

**04, 06, 08, 10, 12, 14, 16, 18, 20, 26, 34, 44**

All dimensions in mm.