
KEMET Part Number: MDC10475K100A54P3TUBE

(F153AA475K100T, MDC100DA7470KA54P3L3)



MDC, Film, Metallized Polyester, Dual-In-Line, 4.7 uF, 10%, 100 V, 63 V, 85C, 10mm



Dimensions	
L	13.5mm +/-0.2mm
W	12.2mm +/-0.2mm
Т	6.05mm +/-0.2mm
S	10mm +/-0.2mm
F	0.5mm +/-0.05mm

Packaging Specifications		
Packaging:	Bulk, Tube	
Packaging Quantity:	35	

General Information		
Supplier:	KEMET	
Series:	MDC	
Dielectric:	Metallized Polyester	
Style:	Dual-In-Line	
RoHS:	Yes	
Lead:	L Leads	

Specifications		
Capacitance:	4.7 uF	
Capacitance Tolerance:	10%	
Voltage DC:	100 VDC	
Voltage AC:	63 VAC	
Temperature Range:	-55/+125C	
Rated Temperature:	85C	
Dissipation Factor:	0.8% 1kHz, 1.5% 10kHz	
Insulation Resistance:	1.0638 GOhms	
Inductance:	4 nH	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

