

PF08128BA

MOS FET Power Amplifier Module for GSM850 and DCS1800/1900 Triple Band Handy Phone

REJ03G0025-0100Z

Rev.1.00

Apr.21.2003


Application

- Triple band amplifier for GSM850 (824 MHz to 849 MHz) and DCS1800/1900 (1710 MHz to 1785 MHz, 1850 MHz to 1910 MHz).
- For 3.5 V & GPRS Class12 operation compatible

Features

- All in one including output matching circuit
- Simple external circuit
- Simple power control
- High gain 3stage amplifier : 0 dBm input Typ
- Lead less thin & Small package : $8 \times 13.75 \times 1.6$ mm Typ
- High efficiency
 - 50% Typ at 35.0 dBm for GSM850
 - 45% Typ at 32.5 dBm for DCS1800
 - 45% Typ at 32.0 dBm for DCS1900
- Lower consume current at low power
 - 100 mA Typ at 7 dBm for GSM850
 - 60 mA Typ at 5 dBm for DCS1800/1900

Pin Arrangement



Absolute Maximum Ratings

(Tc = 25°C)

Item	Symbol	Rating	Unit	Remark
Supply voltage	Vdd	7.0	V	at no-operation
		5.0	V	at operation (50 Ω load)
Supply current	I _{dd} _{GSM}	3.5	A	
	I _{dd} _{DCS}	2	A	
Vctl voltage	Vctl	4	V	
Vapc voltage	Vapc	4	V	
Input power	Pin	10	dBm	
Operating case temperature	Tc (op)	-25 to +100	°C	
Storage temperature	Tstg	-30 to +100	°C	
Output power	P _{out} _{GSM}	5	W	
	P _{out} _{DCS}	3	W	

Note: The maximum ratings shall be valid over both the GSM850-band (824 to 849 MHz), and the DCS1800/1900 band (1710 to 1785 MHz, 1850 to 1910 MHz).

Electrical Characteristics for DC

(Tc = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Drain cutoff current	I _{ds}	—	—	20	μA	Vdd = 4.7 V, Vapc = 0 V, Vctl = 0.2 V
Vapc control current	I _{apc}	—	—	2.0	mA	Vapc = 2.2 V
Vctl control current	I _{ctl}	—	—	2	μA	Vctl = 3 V

Electrical Characteristics for GSM850 band

(Tc = 25°C)

Test conditions unless otherwise noted:

f = 824 to 849 MHz, Vdd1 = Vdd2 = 3.5 V, Pin = 0 dBm, Vctl = 2.0 V, Rg = Rl = 50 Ω, Tc = 25°C,
Pulse operation with pulse width 1154 μs and duty cycle 2:8 shall be used.

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	824	—	849	MHz	
Band select (GSM active)	Vctl	2.0	—	2.8	V	
Input power	Pin	-2	—	2	dBm	
Control voltage range	Vapc	0.2	—	2.2	V	
Supply voltage	Vdd	3.0	3.5	4.5	V	
Total efficiency	η_T	45	50	—	%	Pout _{GSM} = 35 dBm, Vapc controlled
2nd harmonic distortion	2nd H.D.	—	-45	-35	dBc	
3rd harmonic distortion	3rd H.D.	—	-45	-35	dBc	
4th~8th harmonic distortion	4th~8th H.D.	—	—	-35	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Output power (1)	Pout (1)	35.0	36.0	—	dBm	Vapc = 2.2 V
Output power (2)	Pout (2)	33.5	34.5	—	dBm	Vdd = 3.1 V, Vapc = 2.2 V, Tc = +85°C
Idd at Low power	—	—	100	300	mA	Pout _{GSM} = 7 dBm
Isolation	—	—	-50	-37	dBm	Vapc = 0.2 V
Isolation at DCS RF-output when GSM is active	—	—	-25	-18	dBm	Pout _{GSM} = 35 dBm, Measured at f = 1648 to 1698 MHz
Switching time	t _r , t _f	—	1	2	μs	Pout _{GSM} = 5 to 35 dBm
Stability	—	No parasitic oscillation			—	Vdd = 3.1 to 4.5 V, Pout _{GSM} ≤ 35 dBm, Vapc _{GSM} ≤ 2.2 V, Rg = 50 Ω, Tc = 25°C, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	Vdd = 3.1 to 4.5 V, Pout _{GSM} ≤ 35 dBm, Vapc _{GSM} ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Tc = 25°C, Output VSWR = 10 : 1 All phases
Load VSWR tolerance at GPRS CLASS 12 operation	—	No degradation			—	Vdd = 3.1 to 4.2 V, Pout _{GSM} ≤ 35 dBm, Vapc _{GSM} ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Tc ≤ 90°C, Output VSWR = 10 : 1 All phases
Slope Pout/Vapc	—	—	160	200	dB/V	Pout _{GSM} = 5 to 35 dBm
AM output	—	—	15	30	%	Pout _{GSM} = 5 to 35 dBm, 4% AM modulation at input 50 kHz modulation frequency

Electrical Characteristics for DCS1800 band

(Tc = 25°C)

Test conditions unless otherwise noted:

f = 1710 to 1785 MHz, Vdd1 = Vdd2 = 3.5 V, Pin = 0 dBm, Vctl = 0 V, Rg = Rl = 50 Ω, Tc = 25°C, Pulse operation with pulse width 1154 μs and duty cycle 2:8 shall be used.

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	1710	—	1785	MHz	
Band select (DCS active)	Vctl	0	—	0.1	V	
Input power	Pin	-2	—	2	dBm	
Control voltage range	Vapc	0.2	—	2.2	V	
Supply voltage	Vdd	3.0	3.5	4.5	V	
Total efficiency	η_T	40	45	—	%	Pout _{DCS} = 32.5 dBm, Vapc controlled
2nd harmonic distortion	2nd H.D.	—	-45	-35	dBc	
3rd harmonic distortion	3rd H.D.	—	-45	-35	dBc	
4th~8th harmonic distortion	4th~8th H.D.	—	—	-35	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Output power (1)	Pout (1)	32.5	33.5	—	dBm	Vapc = 2.2 V
Output power (2)	Pout (2)	31.0	32.0	—	dBm	Vdd = 3.1 V, Vapc = 2.2 V, Tc = +85°C
Idd at Low power	—	—	60	150	mA	Pout _{DCS} = 5 dBm
Isolation	—	—	-47	-37	dBm	Vapc = 0.2 V
Switching time	t _r , t _f	—	1	2	μs	Pout _{DCS} = 0 to 32.5 dBm
Stability	—	No parasitic oscillation			—	Vdd = 3.1 to 4.5 V, Pout _{DCS} ≤ 32.5 dBm, Vapc ≤ 2.2 V, Rg = 50 Ω, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	Vdd = 3.1 to 4.5 V, Pout _{DCS} ≤ 32.5 dBm, Vapc ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Output VSWR = 10 : 1 All phases
Load VSWR tolerance at GPRS CLASS 12 operation	—	No degradation			—	Vdd = 3.1 to 4.2 V, Pout _{DCS} ≤ 32.5 dBm, Vapc _{DCS} ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Tc ≤ 90°C, Output VSWR = 10 : 1 All phases
Slope Pout/Vapc	—	—	160	200	dB/V	Pout _{DCS} = 0 to 32.5 dBm
AM output	—	—	15	30	%	Pout _{DCS} = 0 to 32.5 dBm, 4% AM modulation at input 50 kHz modulation frequency

Electrical Characteristics for DCS1900 band


(Tc = 25°C)

Test conditions unless otherwise noted:

f = 1850 to 1910 MHz, Vdd1 = Vdd2 = 3.5 V, Pin = 0 dBm, Vctl = 0 V, Rg = Rl = 50 Ω, Tc = 25°C, Pulse operation with pulse width 1154 μs and duty cycle 2:8 shall be used.


Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	1850	—	1910	MHz	
Band select (DCS active)	Vctl	0	—	0.1	V	
Input power	Pin	-2	0	2	dBm	
Control voltage range	Vapc	0.2	—	2.2	V	
Supply voltage	Vdd	3.0	3.5	4.5	V	
Total efficiency	η_T	40	45	—	%	Pout _{DCS} = 32.0 dBm, Vapc controlled
2nd harmonic distortion	2nd H.D.	—	-45	-35	dBc	
3rd harmonic distortion	3rd H.D.	—	-45	-35	dBc	
4th~8th harmonic distortion	4th~8th H.D.	—	—	-35	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Output power (1)	Pout (1)	32.0	33.0	—	dBm	Vapc = 2.2 V
Output power (2)	Pout (2)	30.5	31.5	—	dBm	Vdd = 3.1 V, Vapc = 2.2 V, Tc = +85°C
Idd at Low power	—	—	60	150	mA	Pout _{DCS} = 5 dBm
Isolation	—	—	-47	-37	dBm	Vapc = 0.2 V
Switching time	t _r , t _f	—	1	2	μs	Pout _{DCS} = 0 to 32.0 dBm
Stability	—	No parasitic oscillation			—	Vdd = 3.1 to 4.5 V, Pout _{DCS} ≤ 32.0 dBm, Vapc ≤ 2.2 V, Rg = 50 Ω, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	Vdd = 3.1 to 4.5 V, Pout _{DCS} ≤ 32.0 dBm, Vapc ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Output VSWR = 10 : 1 All phases
Load VSWR tolerance at GPRS CLASS 12 operation	—	No degradation			—	Vdd = 3.1 to 4.2 V, Pout _{DCS} ≤ 32.0 dBm, Vapc ≤ 2.2 V, Rg = 50 Ω, t = 20 sec., Tc ≤ 90°C, Output VSWR = 10 : 1 All phases
Slope Pout/Vapc	—	—	160	200	dB/V	Pout _{DCS} = 0 to 32.0 dBm
AM output	—	—	15	30	%	Pout _{DCS} = 0 to 32.0 dBm, 4% AM modulation at input 50 kHz modulation frequency

Circuit Diagram




Characteristic Curves


GSM mode (824 MHz to 849 MHz)




GSM mode (824 MHz to 849 MHz) (cont.)




DCS mode (1710 MHz to 1785 MHz)




DCS mode (1710 MHz to 1785 MHz) (cont.)



DCS mode (1850 MHz to 1910 MHz)








DCS mode (1850 MHz to 1910 MHz) (cont.)



Package Dimensions

Unit: mm



- 1: Pin_{GSM}
- 2: V_{apc}
- 3: V_{dd1}
- 4: P_{out GSM}
- 5: P_{out DCS}
- 6: V_{dd2}
- 7: V_{ctl}
- 8: Pin_{DCS}
- G: GND

Remark:
Coplanarity of bottom side of terminals are less than 0 ± 0.1 mm.

Package Code	RF-K-8A
JEDEC	—
JEITA	—
Mass (reference value)	—

Renesas Technology Corp. Sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

Keep safety first in your circuit designs!

1. Renesas Technology Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage.
Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of nonflammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

1. These materials are intended as a reference to assist our customers in the selection of the Renesas Technology Corporation product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Renesas Technology Corporation or a third party.
2. Renesas Technology Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
3. All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Renesas Technology Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor for the latest product information before purchasing a product listed herein.
The information described here may contain technical inaccuracies or typographical errors.
Renesas Technology Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.
Please also pay attention to information published by Renesas Technology Corporation by various means, including the Renesas Technology Corporation Semiconductor home page (<http://www.renesas.com>).
4. When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Renesas Technology Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
5. Renesas Technology Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
6. The prior written approval of Renesas Technology Corporation is necessary to reprint or reproduce in whole or in part these materials.
7. If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
8. Please contact Renesas Technology Corporation for further details on these materials or the products contained therein.

RENESAS

<http://www.renesas.com>

Copyright © 2003. Renesas Technology Corporation, All rights reserved. Printed in Japan.
Colophon 0.0